

Ease of use

Remote Panel

The remote panel displays remote UPS status in real time. An additional bar graph shows the current UPS load and remaining capacity in emergency power mode. Besides the visual indicators, the panel has an acoustic alarm (which can be disabled), plus a shutdown contact to enable a remote UPS shutdown in the event of an emergency. The remote panel can be installed at a distance of up to 500 meters. Data and power are supplied to the remote panel over a conventional patch cable. The remote panel is available for Protect C. Tower (6 kVA and higher), Protect 1. and Protect 1.M UPS units.

Key features:

- Robust enclosure with rear wall mounts
- Power supply and data communication over standard Ethernet patch cable (RJ45)
- Can be installed at distances up to 500m
- Acoustic alarm can be enabled to signal critical operating states
- Emergency shutdown contact
- Hot-swappable
- Controlled via slot card (included)
- Clearly structured display indicates current operating state
- No network required



Remote Panel: Technical data

TECHNICAL DATA	
Compatibility	Protect C. (Tower from 6 kVA), Protect 1, Protect 1.M
Includes	Remote Panel, control slot card, user guide
Dimensions	150 mm x 110 mm x 40 mm (W x H x D)
Weight	720 g
AEG part number	600 000 5881

AEG is a registered trademark used under license from AB Electrolux • Specifications are subject to change without notice • 03/2009

AEG Power Solutions GmbH
Emil-Siepmann-Str. 32
59581 Warstein-Belecke
Germany
Tel.: +49 2902 763 168
Fax: +49 2902 763 169
www.aegpartner.net

PERFECT IN FORM AND FUNCTION

AEG